


AGARRAR

EX™




- 1. EX™ - CTL
- 2. Normal
- 3. 22 y 26 mm
- 4. Narrow y Standard
- 5. SYM
- 6. NC, SC y DC

774-960 mm anchura



OF™




- 1. OF™ - CTL
- 2. Normal
- 3. 22 y 26 mm
- 4. Narrow, Standard y Soft
- 5. SYM
- 6. NC, SC y DC

655-906 mm anchura



EVO™



- 1. EVO™ - CTL
- 2. Light y Normal
- 3. 22 y 26 mm
- 4. Narrow, Standard y Soft
- 5. SYM
- 6. NC, SC y DC

695-960 mm anchura



ALL-ROUND

ECO™



- 1. ECO™ - CTL
- 2. Normal
- 3. 22 y 26 mm
- 4. Narrow, Standard y Soft
- 5. SYM
- 6. NC, SC y DC

615-944 mm anchura



KovaX™



- 1. KovaX™ - CTL
- 2. Normal y Plus
- 3. 22 y 26 mm
- 4. Narrow, Standard y Soft
- 5. SYM y OSS
- 6. NC, SC y DC

680-950 mm anchura




Baltic™



- 1. Baltic™ - CTL
- 2. Light y Normal
- 3. 22 y 26 mm
- 4. Narrow, Standard y Soft
- 5. SYM, ASYM y OSS
- 6. NC, SC, DC y RC

650-1210 mm anchura




CoverB™



- 1. CoverB™ - CTL
- 2. Light y Normal
- 3. 22 y 26 mm
- 4. Narrow, Standard y Soft
- 5. SYM, ASYM y OSS
- 6. NC, SC, DC y RC

670-1220 mm anchura



FLOTACIÓN

Skidder Wheel Tracks™

